


Nano-Depth Composition Analyzer

based on Auger Electron Spectroscopy (AES)

Model NDC600



Features:

- High Surface Elemental Sensitivity
- Small Beam Size
- Suitable for Depth Profiling
- Adjustment for Sample Positioning and Retraction
- Compact Design

Description:

Model NDC600 analyzer is the single stage cylindrical mirror analyzer (CMA) comprising of an axial miniature electron gun with robust tungsten filament. The energy resolution of the analyzer is 0.5 %. The signal detector is based on cylindrical slit followed by channel electron multiplier with gain greater than 3×10^{-7} .

The high elemental sensitivity is achieved by combination of high gain - low noise Channeltron™ operated with sophisticated external bandpass filter for Auger signal processing. The Auger's signal detection is from 0.1 nm to 5 nm depth at the substrate surface.

Applications:

Nano-depth composition analyzer, model NDC600 is a simple and convenient surface chemical compositions analysis tool to be used for characterization of a wide range of materials such metals, alloys, oxides, nitrides, and thin films.

Processes such as depth profiling with separate ion sputtering gun model IG70 can be performed. In addition, the diffusion, intercalation and segregation processes can be monitored under the sample cooling and annealing treatments.

Model NDC600

Specifications

Analyzer Type	Single stage cylindrical-mirror analyzer with coaxial electron gun
Energy Resolution:	< 0.5%
Working Distance:	9 mm
Detector:	Channel Electron Multiplier with 1×10^7 - 10^8 gain range
Mounting Flange:	DN100CF(6"CF) conflat flange
Electron Gun	
Type:	Double electrostatic lenses with adjustable focal length and beam diameter
Beam Voltage:	0 - 3 kV
Beam Current:	1 μ A - 5 μ A
Beam Diameter:	100 μ - 250 μ m
Filament:	Tungsten hairpin wire
Beam Deflection:	Electrostatic X-Y axis
Magnetic Shielding:	Mu-metal tube with front cover
Analyzer Length:	Adjustable 250 mm - 350 mm to fit custom chambers
Vacuum Compatibility:	All UHV materials; bake-able to 250°C
Weight:	10 kg

Precision Power Supply: APS300-D and LOA10-AES


APS300-D Digital AES power supply (0 - 3.2 kV) with USB interface and PC control software for Windows 10/11. True primary beam current and total emission measurements. Automatic start-up and shut down, 10 memory settings including outgassing with timer, constant beam current mode.

LOA10-AES Digital AES controller with lock-in amplifier, AES high voltage ramp board 0 - 2.0 kV with precision sine wave oscillator (0.5 - 20 V pk-pk) and AES software for Windows 10/11. USB communication to PC

Ordering Guide

- NDC** Auger electron spectroscopy analyzer, CMA type with axial electron gun on 6" CF (DN100CF) flange
- LMX** Linear motion drive – 50 mm (optional)
- APS300-D** Digital power supply with voltage range 0 – 3.0 kV
- LOA10-AES** Digital AES controller with ramp voltage, sine wave oscillator, lock-in and AES software

Schematic



Data

AES Spectrum from Ag Sample

